



CATEGORY	Type : Deep Recessed Anti-Glare Chrome Fixed Spotlight
PRODUCT CONSTRUCTION	Housing : Aluminum Die Cast Finish : White Ring + Chrome Reflector Protection : IP44
DIMENSION	Diameter : Ø65mm Cut Out : Ø60mm Height : 80mm
OPTICAL SYSTEM	Type : Reflector Beam Direction : Down Tilt : No Beam Angle : 24° 36° Swivel : No Efficiency : High Material : PC
CONTROL	Switching Non Dimmable 1-10 Analog DALI Triac -Leading & Trailing
ELECTRICAL PARAMETER / CHARACTERISTIC	Driver Input Voltage : 100-240V AC 50/60Hz Constant Current Input Power : 7W Output Power: 6W Power Factor : >0.9 THD : <12% Control Gear : Orsam Fulham
LED DETAIL	Light Source Type : COB Light Source Make : Bridgelux Wattage : 6W Driving Current : 40V-125mA Color Temp : 3000K 4000K 6000K Tunable White Color Round Index (CRI) : >80 Lumen : 510lm Efficacy : 85lm/W LED Life : 40,000 Hrs.
APPLICATIONS :	Corporate Office Lobbies & Foyers Retail Sector Commercial & Business Centers etc.



Project Detail: _____
Ref.: _____
Date : _____
Rev : _____

LED Collection

