



CATEGORY	Type : Wall Up-Down Light
PRODUCT CONSTRUCTION	Housing : Aluminum Die Cast Finish : Dark Grey Protection : IP65
DIMENSION	Diameter : Ø62x62mm   Height : 175mm
OPTICAL SYSTEM	Type : Reflector Beam Direction : Up-Down   Tilt : No Beam Angle : 15° / 25° / 60° Swivel : No Efficiency : High Material : PC
CONTROL	Switching Non Dimmable
ELECTRICAL PARAMETER / CHARACTERISTIC	Driver Input Voltage : 100-240V AC 50/60Hz Constant Current Input Power : 2x7W Output Power : 2x6W THD : <12% Power factor : 0.95 Control Gear : Integrated
LED DETAIL	Light Source Type : COB Light Source Make : Bridgelux Wattage : 2x6W Color Temp : 3000K Color Round Index (CRI) : >80 Lumen : 1320lm Efficacy : 110lm/W LED Life : 40,000 Hrs.
APPLICATIONS :	Residential, Building facade, Commercial centres, Passages, Sculptures and Structures



Project Detail: \_\_\_\_\_

Ref.: \_\_\_\_\_

Date : \_\_\_\_\_

Rev : \_\_\_\_\_

LED Collection

