



CATEGORY	Type : Ceiling Surface Down Light
PRODUCT CONSTRUCTION	Housing : Aluminum Die Cast Finish : Dark Grey Protection : IP65
DIMENSION	Diameter : Ø165mm   Height : 300mm
OPTICAL SYSTEM	Type : Reflector Beam Direction : Down   Tilt : No Beam Angle : Medium Swivel : No Efficiency : High Material : PC
CONTROL	Switching Non Dimmable
ELECTRICAL PARAMETER / CHARACTERISTIC	Driver Input Voltage : 100-240V AC 50/60Hz Constant Current Input Power : 33W Output Power : 32W THD : <12% Power Factor : 0.95 Control Gear : Integrated
LED DETAIL	Light Source Type : COB Light Source Make : Bridgelux Wattage : 32W Driving Current : 40V-800mA Color Temp : 3000K Color Round Index (CRI) : >80 Lumen : 3520lm Efficacy : 110lm/W LED Life : 40,000 Hrs.
APPLICATIONS :	Corridors   Hospitality Industry   Corporate   Commercial & Business Centers   Retail Outlets.



Project Detail: \_\_\_\_\_

Ref.: \_\_\_\_\_

Date : \_\_\_\_\_

Rev : \_\_\_\_\_

LED Collection

