



| | |
|---------------------------------------|---|
| CATEGORY | Type : Surface / Spike Mounted Outdoor Light |
| PRODUCT CONSTRUCTION | Housing : Aluminum Die Cast Finish : Dark Grey Protection : IP65 |
| DIMENSION | Diameter : Ø62mm Height : 145mm |
| OPTICAL SYSTEM | Type : Reflector Beam Direction : Up Tilt : Yes Beam Angle : 15° 25° 60° Swivel : No Efficiency : High Material : PC |
| CONTROL | Switching Non Dimmable |
| ELECTRICAL PARAMETER / CHARACTERISTIC | Driver Input Voltage : 100-240V AC 50/60Hz Input Power : 11W/14W Output Power : 10W/13W Power factor : 0.95 THD : <12% Control Gear : Integrated |
| LED DETAIL | Light Source Type : COB Light Source Make : Bridgelux Wattage : 10W/13W Color Temp : 3000K Color Round Index (CRI) : >80 Lumen : 10W-1100lm 13W - 1430lm Efficacy : 110lm/W LED Life : 40,000 Hrs. |
| APPLICATIONS : | Gardens Pathways Parks Sculptures Structures and Landscape lighting. |



Project Detail: _____

Ref.: _____

Date : _____

Rev : _____

LED Collection

