



|                                       |  |
|---------------------------------------|--|
| CATEGORY                              | Type : Surface / Spike Mounted Light   |
| PRODUCT CONSTRUCTION                  | Housing : Aluminum Die Cast<br>Finish : Dark Grey<br>Protection : IP65   |
| DIMENSION                             | Diameter : 60mm   Height : 75mm  |
| OPTICAL SYSTEM                        | Type : Lens<br>Beam Direction : Up   Tilt : Yes<br>Beam Angle : 06°   25°<br>Swivel : No<br>Efficiency : Medium<br>Material : PMMA   |
| CONTROL                               | Switching<br>Non Dimmable  |
| ELECTRICAL PARAMETER / CHARACTERISTIC | Driver Input Voltage : 100-240V AC 50/60Hz<br>Input Power : 11W<br>Output Power : 10W<br>Power factor : 0.95<br>THD : <12%<br>Control Gear : Integrated  |
| LED DETAIL                            | Light Source Type : Hi-Power<br>Light Source Make : Cree<br>Wattage : 10W<br>Color Temp : 3000K<br>Color Round Index (CRI) : >80<br>Lumen : 950lm<br>Efficacy : 95lm/W<br>LED Life : 40,000 Hrs. |
| APPLICATIONS :                        | Pathways   Parks   Sculptures   Gardens   Structures and Landscape lighting  |



Project Detail: \_\_\_\_\_

Ref.: \_\_\_\_\_

Date : \_\_\_\_\_

Rev : \_\_\_\_\_

LED Collection

