



CATEGORY	Type : Outdoor LED Bollard Light
PRODUCT CONSTRUCTION	Housing : Aluminum Die Cast Finish : Dark Grey Protection : IP65
DIMENSION	Dia : 100mm   Height : 300/700/875mm   Optical Part : 35mm
OPTICAL SYSTEM	Type : Clear Optics Beam angle : 360°   Tilt : No Swivel : No Efficiency : High Material : PMMA
CONTROL	Switching Non Dimmable
ELECTRICAL PARAMETER / CHARACTERISTIC	Driver Input Voltage : 100-240V AC 50/60Hz Constant Current Input Power : 11W /13W Output Power : 10W /12W THD : <12% Power Factor : 0.95 Control Gear : Integrated
LED DETAIL	Light Source Type : SMD LED Light Source Make : Bridgelux Wattage : 10W /12W Color Temp : 3000K/4000K/6000K / TW Color Round Index (CRI) : >80 Lumen : 1000lm@10W   1200lm@12W Efficacy : 100lm/W LED Life : 40,000 Hrs.
APPLICATIONS :	Gardens   Landscape   Pathways   Driveways   Entrances   Public areas



Project Detail: \_\_\_\_\_

Ref.: \_\_\_\_\_

Date : \_\_\_\_\_

Rev : \_\_\_\_\_

LED Collection

