



CATEGORY	Type : Outdoor LED Bollard Light
PRODUCT CONSTRUCTION	Housing : Aluminum Die Cast Finish : Dark Grey Protection : IP65
DIMENSION	Dia : 140mm   Height : 350/750/950mm   Optical Part : 98mm
OPTICAL SYSTEM	Type : Milky Diffuser Beam Direction : 360°   Tilt : No Swivel : No Efficiency : Medium Material : PMMA
CONTROL	Switching Non Dimmable
ELECTRICAL PARAMETER / CHARACTERISTIC	Driver Input Voltage : 100-240V AC 50/60Hz Input Power : 16W /21W Output Power : 15W /20W THD : <12% Power Factor : 0.95 Control Gear : Integrated
LED DETAIL	Light Source Type : SMD LED Light Source Make :Bridgelux Wattage : 15W /20W Color Temp : 3000K/4000K/TW Color Round Index (CRI) : >80 Lumen : 1500lm Efficacy : 100lm/W LED Life : 40,000 Hrs.
APPLICATIONS :	Gardens   Landscape   Pathways   Driveways   Entrances   Public areas



Project Detail: \_\_\_\_\_

Ref.: \_\_\_\_\_

Date : \_\_\_\_\_

Rev : \_\_\_\_\_

LED Collection

